

FELT MELANGE




612



642



640



650




641



652




858




651



582




846



859




847



855




848



619




849




635



620



623



610

FELT MELANGE

EN

Composition: 70% Wool, 25% Polyamide, 3% Acrylic, 2% Polyester
Maintenance: Vacuum regularly or professional Dry-clean
Abrasion Resistance: 90.000 Martindale cycles
Flammability: EN 1021 part 1&2
BS 5852-1: 1979

DE

Zusammensetzung: 70% Wolle, 25% Polyamid, 3% Akryl, 2% Polyester
Reinigung: Regelmässig staubsaugen. Professionelle Trockenreinigung
Scheuerfestigkeit: 90.000 Martindale
Feuerschutz: EN 1021 part 1&2
BS 5852-1: 1979

FR

Composition: 70% Laine, 25% Polyamide, 3% Acryl, 2% Polyester
Nettoyage: Aspirer régulièrement. Nettoyage á sec professionnel
Résistance á l'abrasion: 90.000 cycles Martindale
Normes au feu: EN 1021 source d'ignition 1&2
BS 5852-1: 1979

DK

Materiale: 70% Uld, 25% Polyamide, 3% Akryl, 2% Polyester
Rengøring: Støvsug regelmæssigt eller professionel rens
Slidstyrke: 90.000 Martindale
Flammesikring: EN 1021 part 1&2
BS 5852-1: 1979